



Voltage detectors	Medium Voltage	Lines, cabins and substations
-------------------	----------------	-------------------------------

Code: **R-VISOR**



Electronic capacitive detector of MV voltage presence / absence through acoustic and visual signals clearly visible from bottom and lateral side of the detector



In conformity with	IEC 61243-1
--------------------	-------------

Range	3 ÷ 10 KV
	6 ÷ 12 KV
	10 ÷ 30 KV
	15 ÷ 45 KV
	22 ÷ 66 KV

Group: III
 Category: L
 Frequency: 50 ~ 60 Hz
 Climatic category: N

- Suitable for use in wet condition, either indoors or outdoors.
- Double indication of operative voltage presence: intermittent acoustic and flashing of red LEDs in the lower and lateral side of the detector.
- The absence of operative voltage is indicated by green permanent LEDs on in the lower and lateral side of the detector.
- The lighting of the orange led-light is the indication of low battery.
- Built-in self-control check for testing the accurate working of the voltage detector before use.
- Cylindrical box made of ABS, diameter 58 mm.
- V-shape metallic contact probe.
- Supply: alkaline battery 9 V (2 included).
- Carrying case with internal foam housing.
- Other voltage ranges to be set in base at working voltage.

Alternative attacks:



U	M10	CH12
---	-----	------