



WebLog 250

Art.No.: WEBLOG250

- ◎ M-Bus data logger for 250 or 120 meters
- ◎ 7" LED Touchscreen
- ◎ Remote readout via web browser
- ◎ USB, Ethernet, W-LAN, RS232C, Modem (analogue/GPRS)
- ◎ Data export as XML, XLSX, CSV via E-Mail, FTP, USB
- 86 x 234 x 264 mm
- 800 x 480 Pixel Touchscreen
- Wall mounted or DIN rail TS35
- RS232C
- integrated power supply (110 - 250 V)
- 1 GB memory

Central Unit 250 / 120

Art.No.: DR001 / DR001

- ◎ M-Bus data logger for 250 or 120 slaves
- ◎ Operation on-site by keyboard and LCD
- ◎ Export of measured data to PC database
- ◎ Service and modem interface
- 85 x 200 x 240 mm
- Wall mounted
- RS232C
- external Modem (e.g. MOD001)
- plug-in, wall mounted or DIN rail power supply (scope of delivery)
- 256kB memory

W60 Data Logger

Art.No.: MR004DL

- ◎ M-Bus data logger for 60 slaves
- ◎ Level converter for 60 slaves
- ◎ Operation on-site by keyboard and LCD
- ◎ Integrated power supply
- 71 x 165 x 175 mm
- Wall mounted
- RS232C and RS485
- external modem (e.g. MOD001)
- 230V or 110V power supply selectable
- 512kB memory

W60 Remote Display

Art.No.: MR004FA

- ◎ M-Bus remote display for 60 slaves
- ◎ Level converter for 60 slaves
- ◎ Operation on-site by keyboard and LCD
- ◎ Integrated power supply
- 71 x 165 x 175 mm
- Wall mounted
- RS232C and RS485
- external modem (e.g. MOD001)
- 230V or 110V power supply selectable



C20 Data Logger

Art.No.: MR006DL

- ◎ M-Bus Data logger for 20 slaves
- ◎ Level converter for 20 slaves
- ◎ Operation on-site by keyboard and LCD
- ◎ Rail mounted
- 58 x 106 x 96 mm
- Mounted on DIN rail TS35
- RS232C
- external modem (e.g. MOD001)
- external power supply 12 .. 24 V (not in scope of delivery)
- 1MB memory optional 2MB/4MB

C20 Remote Display

Art.No.: MR006FA

- ◎ M-Bus remote display for 20 slaves
- ◎ Level converter for 20 slaves
- ◎ Operation on-site by keyboard and LCD
- ◎ Rail mounted
- 58 x 106 x 96 mm
- Mounted on DIN rail TS35
- RS232C
- external modem
- external power supply 12 .. 24 V (not in scope of delivery)

C3 Data Logger

Art.No.: MR005DL

- ◎ M-Bus Data logger for 3 slaves
- ◎ Level converter for 3 slaves
- ◎ Operation on-site by keyboard and LCD
- ◎ Rail mounted
- 558 x 106 x 96 mm
- Mounted on DIN rail TS35
- RS232C
- external modem (e.g. MOD001)
- external power supply 12 .. 24 V (not in scope of delivery)
- 1MB memory optional 2MB/4MB

C3 Remote Display

Art.No.: MR005FA

- ◎ M-Bus remote display for 3 slaves
- ◎ Level converter for 3 slaves
- ◎ Operation on-site by keyboard and LCD
- ◎ Rail mounted
- 58 x 106 x 96 mm
- Mounted on DIN rail TS35
- RS232C
- external modem
- external 24V power supply (not in scope of delivery)



M-Bus Level Converter

Art.No.: PW250

- ◎ M-Bus converter for up to 250 slaves
- ◎ Repeater for M-Bus extension: up to 250 slaves or cable network
- ◎ Intelligent interface management

- 264 x 234 x 86 mm
- Wall mounted or DIN rail TS35
- 10/100 Mbit Ethernet, USB-Device, RS232 (SUB-D9), RS232C (Klemme), RS485, Repeater (M-Bus IN)
- integrated 110 ... 250V power supply

M-Bus Level Converter

Art.No.: DR003/DR004/DR005/DR006

- ◎ RS232C Interface, 250 Slaves (DR003)
- ◎ RS232C Interface, 120 Slaves (DR004)
- ◎ RS485 Interface, 250 Slaves (DR005)
- ◎ RS485 Interface, 120 Slaves (DR006)

- 85 x 200 x 240 mm
- Wall mounted
- RS485 or RS232C
- plug-in, wall mounted or DIN rail power supply (scope of delivery)

Repeater

Art.No.: DR007

- ◎ M-Bus repeater for 250 slaves
- ◎ Increases the number of possible slaves by 250
- ◎ Increases the M-Bus extension (cable)

- 85 x 200 x 240 mm
- Wall mounted
- plug-in, wall mounted or DIN rail power supply (scope of delivery)

Micromaster

Art.No.: MR003 / MR003 USB

- ◎ Portable M-Bus level converter for 10 slaves
- ◎ Power supply by laptop
- ◎ Versions with RS232C or USB interface available

- 30 x 54 x 110 mm
 - RS232C or USB interface
 - Power supply by laptop
- Delivery contains:
- **MR003:** special cable
 - **MR003USB:** USB cable
 - Device driver for Windows



W60 Level Converter

Art.No.: MR004W

- ◎ M-Bus level converter for 60 slaves
- ◎ RS232C and RS485 interface
- ◎ Integrated power supply

- 71 x 165 x 175 mm
- Wall mounted
- RS232C
- external modem
- integrated 230V or 110V power supply

PW60

Art.No.: MR004C

- ◎ M-Bus level converter for 60 slaves
- ◎ RS232C and RS485 interface
- ◎ IR-opto-interface

- 78 x 70 x 118 mm
- Mounted on DIN rail TS35
- RS232C, RS485 and IR-opto-interface
- external power supply 12 .. 24 V (not in scope of delivery)

PW20

Art.No.: MR006 / MR006IR

- ◎ M-Bus level converter for 20 slaves
- ◎ RS232C interface
- ◎ additional IR-opto-interface at the MR006IR

- 78 x 55 x 118 mm
- Mounted on DIN rail TS35
- RS232C or RS232C and additional IR-opto-interface
- external power supply 12 .. 24 V (not in scope of delivery)

PW3

Art.No.: MR005 / MR005IR

- ◎ M-Bus level converter for 3 slaves
- ◎ RS232C interface
- ◎ additional IR-opto-interface at the MR005IR

- 78 x 55 x 118 mm
- Mounted on DIN rail TS35
- RS232C or RS232C and additional IR-opto-interface
- external power supply 12 .. 24 V (not in scope of delivery)