

# Technical Product Data Sheet



## Smartline

Personal Evacuation Device



012230066 40m

### DESCRIPTION

### TECHNICAL SPECIFICATION

#### Physical properties

<b>Material device:</b>	Aluminium
<b>Function:</b>	Manual descent device
<b>Mechanics:</b>	Friction brake

<b>Lifting mechanics:</b>	Method 1:3
<b>Rope:</b>	Aramid rope plaited, 5.5mm. Sheet of Aramid
<b>Rope Weight:</b>	15g/m
<b>Attaching connector, device:</b>	Aluminium carabiner with screw gate
<b>Attaching connector, rope:</b>	Aluminium carabiner with screw gate
<b>Kit:</b>	Seal in bag with 1 pc anchor sling 1,6m, knife, small user instruction

## Segments

<b>Segments:</b>	Wind, Telecom, Tower, Pole, Oil & Gas, Cranes, offshore, skylifts, many more
------------------	--

## Standards

<b>Standards:</b>	EN341:1992
<b>Notified Body:</b>	SGS United Kingdom Ltd.,: Unit 202B Worle Parkway, Weston-super-Mare, BS22 6WA, UK

## Lifespan and other information

<b>Lifespan device:</b>	10 Years
<b>Lifespan rope:</b>	7 years lifespan maximum working life
<b>Max. load:</b>	140kg
<b>Min. load:</b>	30kg
<b>Descent speed:</b>	0.5-2m/s
<b>Max. rope length:</b>	80m
<b>Max. descent distance:</b>	80m
<b>Working temperatures:</b>	-40-(+50)°C
<b>Inspection requirements:</b>	Yearly inspection

**Identification:**


Serial Number

**RFID:**

NO

**User instruction languages:**

ENG, SV, DK, NB, FI, DE, IT, FR, ES, CH, PL



Lägatan 63, 302 63 Halmstad, Sweden

Tel. +46 10 45 47 500 | Fax. +46 10 45 47 501

support@cresto.se | www.cresto.com