

SMARTLINE X

Evacuation equipment

- Compact personal equipment
- Maximal user weight 140 kg
- Can be mounted on the harness

Standards: **EN 341 : 2011**



Product description

Our own personal evacuation equipment Smartline X is one of the worlds smallest evacuation device on the market with a remarkable capacity of 140 kg user weight.

Smartline X kit is developed especially for pole and tower workers but can also be used for most evacuations and rescues for heights up to 25 meters. Smartline X, with its great capacity, although in small size and low weight, enables you always to carry it on your harness for your safety. Smartline X is a small, manually controlled descent device for evacuation. It can also thanks to the special shackle easily be configured for lifting a person shorter distances in a rescue.

The precision put into the details of this product is extraordinary. The line used in the device is made out of Aramide, which has fantastic durability. The cooling plates on the side make sure to keep the device and rope from overheating.

The Smartline X is certified to the PPE Regulation and in accordance with the EN 341 standard for one time use.

Material shortages due to the pandemic have resulted in the need for Cresto Group to periodically and temporarily replace certain components on our products with replacement components fulfilling the same function. Due to this, the product images may differ from that which is delivered.

Product properties

Brand:	RESQ
Material:	Aluminum , Nylon, Aramid
Minimum load (kg):	60
Maximum load (kg):	140
Maximum number of users:	1
Minimum working temperature (c):	-25
Maximum working temperature (c):	50
EN-standard:	EN 341 : 2011
Notified body:	0200, FORCE Certification A/S, Main office, Park Allé 345, DK-2605 Brøndby, Denmark
Annual inspection:	Yes, every 12 months
Life span:	7 years
RFID:	Yes

Warranty:	2 year
Declaration of Conformity:	Yes
Rope:	Aramid 5,5mm, 16 twill braid coreless construction
Maximum rope length (m):	200
Fall indicator:	No
Maximum descent:	200 meter
Descent speed (m/s):	0,5-2
Energy absorber:	Yes
Gate opening (mm):	20
Attaching connector 1:	Device: Aluminum carabiner tri-lock
Attaching connector 2:	Rope/absorber: Aluminum carabiner tri-lock
Functions:	Descend function
Mechanics:	Friction b rake
Lifting mechanics:	Method 1:3
Adjustable under load:	Yes

Reference	Article name	Size (m)	Colors	GTIN	Country of origin
012230117	RESQ, Smartline X, 15m	15	BLACK	7350015798502	Slovakia
012230118	RESQ, Smartline X, 25m	25	BLACK	7350015798519	Slovakia