



Fuse-link, high speed, 250 A, AC 500 V, 55 x 55 x 140 mm, aR, IEC, with indicator



Part no. FUSE 250A 500V TP 405 AR
 Catalog No. 170E2095

Delivery program

Product range			Fuse
Basic function			Fuse-link
Field of application			high speed
Rated current	I	A	250
Rated voltage			AC 500 V
Size			55 x 55 x 140 mm
Utilization category			aR
Status indicator			with indicator
usable for size/applications			diode protection
Standard/Approval			IEC
Shape			square body with centre-bolted tags

Technical data ETIM 7.0

Circuit breakers and fuses (EG000020) / Low Voltage HRC fuse (EC000055)			
Electric engineering, automation, process control engineering / Electrical installation, device / Safety fuse inserts / Low-Voltage HRC fuse (ecl@ss10.0.1-27-14-20-05 [AFZ800015])			
Construction size			Other
Rated current		A	250
Rated voltage		V	500
Voltage type			AC
Rated switching capacity		kA	220
Utilization category			aR (accompanied semiconductor protection)
Type of fuse status indicator			Top fuse status indicator
Insulated metal gripping lugs (IMGL)			No

Additional product information (links)

Product datasheet (pdf)	http://www1.cooperbusmann.com/pdf/4a317260-8e98-40d9-b43b-e80c53a102f6.pdf
-------------------------	---