

### Tralift™ Cleantech

#### Manual stainless steel chain hoist

Réf.: T-3739/EN Révision: 01 Date: 04/2023



The Tralift™ Cleantech is a stainless steel chain hoist. It allows to lift and lower a load fixed to the lifting hook by means of human force applied to the hand chain. The device is anchored to a fixed attachment point or an interface (ex: Corso trolley)\* with the suspension hook.

\* Some informations on the trolleys of the Corso range can be obtained on simple request to Tractel® or on the website www.tractel.com.

### **APPLICATIONS**


- Food industry
- Pharmaceutical
- Cosmetic

- Aggressive environment (seaside, dusty)
- Clean room


### **TECHNICAL CHARACTERISTICS**

- Compact and light device,
- 360° rotating hooks marked with the WLL\* of the hoist and fitted with safety latches,
- Standard lifting stroke: 3 m,
- Components in stainless steel:
  - Pulley block
  - Hand wheel
  - Casings
  - Plates
  - Lifting hook


- Suspension hook
- Sheave block
- Screws
- Lifting chain
- Hand chain
- High performance grease compatible with food industry (Mobilgrease FM 222)
- Designed and built to withstand dynamic tests at 1.1 x WLL\*, static at 1.5 x WLL\* and to guarantee a minimum mechanical resistance of 4 x WLL\*







WLL\*: 2t



WLL*(t)		0.5	1	2
Standard lifting height (m) (**)		3		
Minimum distance between hook H min (mm)		376	376	425
Tensile stress on hand chain at WLL* (daN)		15	31	34
Number of strands (load chain)		1	1	2
Measurements Ø × D (see fig.1) of load chain (mm)		6x18	7x21	7x21
Measurements Ø x D (see fig.1) of hand chain (mm)		5x23.3		
Dimensions (mm)	А	172	172	192
	В	151	151	151
	С	26	26	34
	D	40	40	50
Net weight (kg)		11,4	14,0	21,1
Additional weight per m. lifted (kg)			2,0	3,1

<sup>\*</sup> WLL = Working Load Limit.

<sup>\*\*:</sup> other lengths available by pitch of 1 m.



## **Tralift™ Cleantech**

Manual stainless steel chain hoist

**Réf**. : T-3739/EN **Révision** : 01 **Date** : 04/2023

## **APPLICABLE STANDARDS**

- European directive 2006/42/CE
- The Supply of Machinery (Safety) Regulations 2008 (SI 2008/1597) of the United Kingdom Machinery directive

# PRODUCT CODE AND LOGISTIC INFORMATION

Code	Description	Code EAN	Net Weight	Weight (packaging incl.)	Packaging dimensions
294899	Tralift Cleantech 0,5t 3m	3600232948995	11,4 kg	11,7 kg	23 x 15 x 19 cm
294909	Tralift Cleantech 1t 3m	3600232949091	14,0 kg	14,4 kg	26 x 17 x 19 cm
294919	Tralift Cleantech 2t2b 3m	3600232949190	21,1 kg	21,6 kg	31 x 20 x 24 cm

Other configurations: consult us